

Scheda Dati

080E160-P3

Drukknopkast 90x160, 3 gaten Ø 22



Caratteristiche

Bereik	Ergonomische drukknopkasten 90 mm
Componente	Ergonomische Drukknopkast 90x160 mm
Rubriek	080E160-P3
Omschrijving	Drukknopkast 90x160, 3 gaten Ø 22
Kleur	Grigio RAL7016 / Grigio RAL7035
Peso	182,0
Tariffa doganale	85381000
GTIN	8052878071950

Dati tecnici

Approvals	CE
Compliance with standards	IEC-EN62208
Operating temperatures	-25° ÷ +70°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK07 (IEC-EN62262)
Housing material	High impact grade thermoplastic polymer
Manufacturing process	Injection moulding
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Screw type	Torx T15 slotted head type
Tightening torque	0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Heavy metal-free	yes
PVC-free	yes
Silicon-free	yes
Halogen-free	yes
Combustion behaviour	HB (UL94)
Combustion behaviour	650°(IEC-EN60695-2-11)
Fitted for outdoor application	yes
Pushbutton selection	See 020 product range: 020 SM2 Command&Signalling;
Warranty period	18 months

Disegni tecnici
