

## Scheda Dati

080E160-P3

Caixa botoeira 90x160, 3 furos Ø 22



## Caratteristiche

<b>Gama</b>	Caixas botoeiras ergonômicas 90 mm
<b>Componente</b>	Caixa botoeira ergonômica 90x160 mm
<b>Código</b>	080E160-P3
<b>Descrição</b>	Caixa botoeira 90x160, 3 furos Ø 22
<b>Cor</b>	Grigio RAL7016 / Grigio RAL7035
<b>Peso</b>	182,0
<b>Tariffa doganale</b>	85381000
<b>GTIN</b>	8052878071950

## Dati tecnici

<b>Approvals</b>	CE
<b>Compliance with standards</b>	IEC-EN62208
<b>Operating temperatures</b>	-25° ÷ +70°C
<b>Protection degree</b>	IP66 - IP69 (IEC-EN60529)
<b>Protection against impact</b>	IK07 (IEC-EN62262)
<b>Housing material</b>	High impact grade thermoplastic polymer
<b>Manufacturing process</b>	Injection moulding
<b>Gasket material</b>	TPE thermoplastic elastomer
<b>Screw material</b>	Stainless steel AISI 304
<b>Screw type</b>	Torx T15 slotted head type
<b>Tightening torque</b>	0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in)
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Heavy metal-free</b>	yes
<b>PVC-free</b>	yes
<b>Silicon-free</b>	yes
<b>Halogen-free</b>	yes
<b>Combustion behaviour</b>	HB (UL94)
<b>Combustion behaviour</b>	650°(IEC-EN60695-2-11)
<b>Fitted for outdoor application</b>	yes
<b>Pushbutton selection</b>	See 020 product range: 020 SM2 Command&Signalling;
<b>Warranty period</b>	18 months

## Disegni tecnici

---