

Scheda Dati

080E90-GP1

Drukknopkast 90x90, 1 gat Ø 22, geel



Caratteristiche

| | |
|-------------------------|--------------------------------------|
| Bereik | Ergonomische drukknopkasten 90 mm |
| Componente | Ergonomische Drukknopkast 90x90 mm |
| Rubriek | 080E90-GP1 |
| Omschrijving | Drukknopkast 90x90, 1 gat Ø 22, geel |
| Kleur | Giallo RAL1003 / Grigio RAL7035 |
| Peso | 130,0 |
| Tariffa doganale | 85381000 |
| GTIN | 8052878064969 |

Dati tecnici

| | |
|--|--|
| Approvals | CE, EAC |
| Compliance with standards | IEC-EN62208 |
| Operating temperatures | -25° ÷ +70°C |
| Protection degree | IP66 - IP69 (IEC-EN60529) |
| Protection against impact | IK07 (IEC-EN62262) |
| Housing material | High impact grade thermoplastic polymer |
| Manufacturing process | Injection moulding |
| Gasket material | TPE thermoplastic elastomer |
| Screw material | Stainless steel AISI 304 |
| Screw type | Torx T15 slotted head type |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Heavy metal-free | yes |
| PVC-free | yes |
| Silicon-free | yes |
| Halogen-free | yes |
| Combustion behaviour | HB (UL94) |
| Combustion behaviour | 650°(IEC-EN60695-2-11) |
| Fitted for outdoor application | yes |
| Pushbutton selection | See 020 product range: 020 SM2 Command&Signalling; |
| Warranty period | 18 months |

Disegni tecnici

