

Datenblatt

080E90-P2

Bedienpult-Gehäuse 90x90, 2 Bohrungen Ø 22



Merkmale

| | |
|------------------------|--|
| Baureihe | Ergonomische Drucktaster-Gehäuse 90 mm |
| Komponenten | Ergonomisches Bedienpult-Gehäuse 90x90 mm |
| Artikel-Nr. | 080E90-P2 |
| Beschreibung | Bedienpult-Gehäuse 90x90, 2 Bohrungen Ø 22 |
| Farbe | Grigio RAL7016 / Grigio RAL7035 |
| Gewicht - gr | 130,0 |
| Zolltarifnummer | 85381000 |
| GTIN | 8052878064976 |

Technische Daten

| | |
|--|--|
| Approvals | CE, EAC |
| Compliance with standards | IEC-EN62208 |
| Operating temperatures | -25° ÷ +70°C |
| Protection degree | IP66 - IP69 (IEC-EN60529) |
| Protection against impact | IK07 (IEC-EN62262) |
| Housing material | High impact grade thermoplastic polymer |
| Manufacturing process | Injection moulding |
| Gasket material | TPE thermoplastic elastomer |
| Screw material | Stainless steel AISI 304 |
| Screw type | Torx T15 slotted head type |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Heavy metal-free | yes |
| PVC-free | yes |
| Silicon-free | yes |
| Halogen-free | yes |
| Combustion behaviour | HB (UL94) |
| Combustion behaviour | 650°(IEC-EN60695-2-11) |
| Fitted for outdoor application | yes |
| Pushbutton selection | See 020 product range: 020 SM2 Command&Signalling; |
| Warranty period | 18 months |

Technische Zeichnungen

