

Hoja de datos

080EU160-P3

Caja botonera 90x160, 3 orificios Ø 22 , UL



Características

Rango	Cajas botoneras ergonómicas 90 mm
Componente	Caja botonera ergonómica 90x160 mm
Código	080EU160-P3
Descripción	Caja botonera 90x160, 3 orificios Ø 22 , UL
Color	Grigio RAL7016 / Grigio RAL7035
Peso	182,0
Arancel aduanero	85381000
GTIN	8052878071615

Datos técnicos

Approvals	CE, UL, CSA, EAC
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Operating temperatures	-25° ÷ +70°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK07 (IEC-EN62262)
Housing material	High impact grade thermoplastic polymer
Manufacturing process	Injection moulding
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Screw type	Torx T15 slotted head type
Combustion behaviour	V0 (UL94)
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Heavy metal-free	yes
PVC-free	yes
Silicon-free	yes
Halogen-free	yes
Fitted for outdoor application	yes
Combustion behaviour	96°(IEC-EN60695-2-12)
Pushbutton selection	See 020 product range: 020 SM2 Command&Signalling;
Warranty period	18 months

Dibujos técnicos

