

Fiche technique

080EU225-P6

Boîte à boutons 90x225, 6 trous Ø 22 , UL



Caractéristiques

| | |
|-------------------------------------|---|
| Portée | Boîtes à boutons ergonomiques 90 mm |
| Composant | Boîte à boutons ergonomique 90x225 mm |
| Code | 080EU225-P6 |
| Désignation des marchandises | Boîte à boutons 90x225, 6 trous Ø 22 , UL |
| Couleur | Grigio RAL7016 / Grigio RAL7035 |
| Poids | 225,0 |
| Tarif douanier | 85381000 |
| GTIN | 8052878071639 |

Données techniques

| | |
|--|--|
| Approvals | CE, UL, CSA, EAC |
| Compliance with standards | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| Operating temperatures | -25° ÷ +70°C |
| Protection degree | IP66 - IP69 (IEC-EN60529) |
| Protection against impact | IK07 (IEC-EN62262) |
| Housing material | High impact grade thermoplastic polymer |
| Manufacturing process | Injection moulding |
| Gasket material | TPE thermoplastic elastomer |
| Screw material | Stainless steel AISI 304 |
| Screw type | Torx T15 slotted head type |
| Combustion behaviour | V0 (UL94) |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Heavy metal-free | yes |
| PVC-free | yes |
| Silicon-free | yes |
| Halogen-free | yes |
| Fitted for outdoor application | yes |
| Combustion behaviour | 96°(IEC-EN60695-2-12) |
| Pushbutton selection | See 020 product range: 020 SM2 Command&Signalling; |
| Warranty period | 18 months |

Dessins techniques

