

## Scheda Dati

080EU225-P6

Scatola pulsantiera 90x225, 6 fori Ø 22 , UL



## Caratteristiche

<b>Gamma</b>	Scatole pulsantiere ergonomiche 90 mm
<b>Componente</b>	Scatola pulsantiera ergonomica 90x225 mm
<b>Codice</b>	080EU225-P6
<b>Descrizione</b>	Scatola pulsantiera 90x225, 6 fori Ø 22
<b>Colore</b>	Grigio RAL7016 / Grigio RAL7035
<b>Peso</b>	225,0
<b>Tariffa doganale</b>	85381000
<b>GTIN</b>	8052878071639

## Dati tecnici

<b>Approvals</b>	CE, UL, CSA, EAC
<b>Compliance with standards</b>	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
<b>Operating temperatures</b>	-25° ÷ +70°C
<b>Protection degree</b>	IP66 - IP69 (IEC-EN60529)
<b>Protection against impact</b>	IK07 (IEC-EN62262)
<b>Housing material</b>	High impact grade thermoplastic polymer
<b>Manufacturing process</b>	Injection moulding
<b>Gasket material</b>	TPE thermoplastic elastomer
<b>Screw material</b>	Stainless steel AISI 304
<b>Screw type</b>	Torx T15 slotted head type
<b>Combustion behaviour</b>	V0 (UL94)
<b>Tightening torque</b>	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Heavy metal-free</b>	yes
<b>PVC-free</b>	yes
<b>Silicon-free</b>	yes
<b>Halogen-free</b>	yes
<b>Fitted for outdoor application</b>	yes
<b>Combustion behaviour</b>	960°(IEC-EN60695-2-12)
<b>Pushbutton selection</b>	See 020 product range: 020 SM2 Command&Signalling;
<b>Warranty period</b>	18 months

## Disegni tecnici

