

Datablad

080EU225-P6

Drukknopkast 90x225, 6 gaten Ø 22 , UL



Kenmerken

Bereik	Ergonomische drukknoopkasten 90 mm
Component	Ergonomische Drukknopkast 90x225 mm
Rubriek	080EU225-P6
Omschrijving	Drukknopkast 90x225, 6 gaten Ø 22 , UL
Kleur	Grigio RAL7016 / Grigio RAL7035
Gewicht	225,0
Douanetarief	85381000
GTIN	8052878071639

Technische gegevens

Approvals	CE, UL, CSA, EAC
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Operating temperatures	-25° ÷ +70°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK07 (IEC-EN62262)
Housing material	High impact grade thermoplastic polymer
Manufacturing process	Injection moulding
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Screw type	Torx T15 slotted head type
Combustion behaviour	V0 (UL94)
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Heavy metal-free	yes
PVC-free	yes
Silicon-free	yes
Halogen-free	yes
Fitted for outdoor application	yes
Combustion behaviour	96°(IEC-EN60695-2-12)
Pushbutton selection	See 020 product range: 020 SM2 Command&Signalling;
Warranty period	18 months

Technische tekeningen

