

Fiche technique

080EU290-P8  
Boîte à boutons 90x290, 8 trous Ø 22 , UL



Caractéristiques

|                              |                                           |
|------------------------------|-------------------------------------------|
| Portée                       | Boîtes à boutons ergonomiques 90 mm       |
| Composant                    | Boîte à boutons ergonomique 90x290 mm     |
| Code                         | 080EU290-P8                               |
| Désignation des marchandises | Boîte à boutons 90x290, 8 trous Ø 22 , UL |
| Couleur                      | Grigio RAL7016 / Grigio RAL7035           |
| Poids                        | 290,0                                     |
| Tarif douanier               | 85381000                                  |
| GTIN                         | 8052878071646                             |

Données techniques

|                                   |                                                    |
|-----------------------------------|----------------------------------------------------|
| Approvals                         | CE, UL, CSA, EAC                                   |
| Compliance with standards         | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2   |
| Operating temperatures            | -25° ÷ +70°C                                       |
| Protection degree                 | IP66 - IP69 (IEC-EN60529)                          |
| Protection against impact         | IK07 (IEC-EN62262)                                 |
| Housing material                  | High impact grade thermoplastic polymer            |
| Manufacturing process             | Injection moulding                                 |
| Gasket material                   | TPE thermoplastic elastomer                        |
| Screw material                    | Stainless steel AISI 304                           |
| Screw type                        | Torx T15 slotted head type                         |
| Combustion behaviour              | V0 (UL94)                                          |
| Tightening torque                 | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)                        |
| Protection against electric shock | Class II (IEC-EN61140)                             |
| Heavy metal-free                  | yes                                                |
| PVC-free                          | yes                                                |
| Silicon-free                      | yes                                                |
| Halogen-free                      | yes                                                |
| Combustion behaviour              | 960°(IEC-EN60695-2-12)                             |
| Fitted for outdoor application    | yes                                                |
| Pushbutton selection              | See 020 product range: 020 SM2 Command&Signalling; |
| Warranty period                   | 18 months                                          |

# Dessins techniques

