

## Datenblatt

080EU90-GP1

Bedienpult-Gehäuse 90x90, 1 Bohrung Ø 22, gelb , UL



## Merkmale

|                        |   |
|------------------------|---|
| <b>Baureihe</b>        | Ergonomische Drucktaster-Gehäuse 90 mm              |
| <b>Komponenten</b>     | Ergonomisches Bedienpult-Gehäuse 90x90 mm           |
| <b>Artikel-Nr.</b>     | 080EU90-GP1   |
| <b>Beschreibung</b>    | Bedienpult-Gehäuse 90x90, 1 Bohrung Ø 22, gelb , UL |
| <b>Farbe</b>           | Giallo RAL1003 / Grigio RAL7035                     |
| <b>Gewicht - gr</b>    | 130,0   |
| <b>Zolltarifnummer</b> | 85381000  |
| <b>GTIN</b>            | 8052878071592                                       |

## Technische Daten

|  |  |
|--|--|
| <b>Approvals</b>                         | CE, UL, CSA, EAC                                   |
| <b>Compliance with standards</b>         | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2   |
| <b>Operating temperatures</b>            | -25° ÷ +70°C                                       |
| <b>Protection degree</b>                 | IP66 - IP69 (IEC-EN60529)                          |
| <b>Protection against impact</b>         | IK07 (IEC-EN62262)                                 |
| <b>Housing material</b>                  | High impact grade thermoplastic polymer            |
| <b>Manufacturing process</b>             | Injection moulding                                 |
| <b>Gasket material</b>                   | TPE thermoplastic elastomer                        |
| <b>Screw material</b>                    | Stainless steel AISI 304                           |
| <b>Screw type</b>                        | Torx T15 slotted head type                         |
| <b>Combustion behaviour</b>              | V0 (UL94)  |
| <b>Tightening torque</b>                 | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)                        |
| <b>Protection against electric shock</b> | Class II (IEC-EN61140)                             |
| <b>Heavy metal-free</b>                  | yes  |
| <b>PVC-free</b>                          | yes  |
| <b>Silicon-free</b>                      | yes  |
| <b>Halogen-free</b>                      | yes  |
| <b>Fitted for outdoor application</b>    | yes  |
| <b>Combustion behaviour</b>              | 960°(IEC-EN60695-2-12)                             |
| <b>Pushbutton selection</b>              | See 020 product range: 020 SM2 Command&Signalling; |
| <b>Warranty period</b>                   | 18 months  |

## Technische Zeichnungen

