

Datablad

080EU90-GP1

Drukknopkast 90x90, 1 gat Ø 22, geel , UL



Kenmerken

Bereik	Ergonomische drukknoopkasten 90 mm
Component	Ergonomische Drukknopkast 90x90 mm
Rubriek	080EU90-GP1
Omschrijving	Drukknopkast 90x90, 1 gat Ø 22, geel , UL
Kleur	Giallo RAL1003 / Grigio RAL7035
Gewicht	130,0
Douanetarief	85381000
GTIN	8052878071592

Technische gegevens

Approvals	CE, UL, CSA, EAC
Compliance with standards	IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2
Operating temperatures	-25° ÷ +70°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK07 (IEC-EN62262)
Housing material	High impact grade thermoplastic polymer
Manufacturing process	Injection moulding
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Screw type	Torx T15 slotted head type
Combustion behaviour	V0 (UL94)
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Heavy metal-free	yes
PVC-free	yes
Silicon-free	yes
Halogen-free	yes
Fitted for outdoor application	yes
Combustion behaviour	96°(IEC-EN60695-2-12)
Pushbutton selection	See 020 product range: 020 SM2 Command&Signalling;
Warranty period	18 months

Technische tekeningen

