# Scheda Dati

080EU90-P1
Scatola pulsantiera 90x90, 1 foro Ø 22 , UL





## Caratteristiche

| | |
|---|---|
| **Gamma** | Scatole pulsantiere ergonomiche 90 mm |
| **Componente** | Scatola pulsantiera ergonomica 90x90 mm |
| **Codice** | 080EU90-P1 |
| **Descrizione** | Scatola pulsantiera 90x90, 1 foro Ø 22 |
| **Colore** | Grigio RAL7016 / Grigio RAL7035 |
| **Peso** | 130,0 |
| **Tariffa doganale** | 85381000 |
| **GTIN** | 8052878071585 |

## Dati tecnici

| | |
|---|---|
| **Approvals** | CE, UL, CSA, EAC |
| **Compliance with standards** | IEC-EN60947-1, IEC-EN60947-5-1, UL508, CSA C22-2 |
| **Operating temperatures** | -25° ÷ +70°C |
| **Protection degree** | IP66 - IP69 (IEC-EN60529) |
| **Protection against impact** | IK07 (IEC-EN62262) |
| **Housing material** | High impact grade thermoplastic polymer |
| **Manufacturing process** | Injection moulding |
| **Gasket material** | TPE thermoplastic elastomer |
| **Screw material** | Stainless steel AISI 304 |
| **Screw type** | Torx T15 slotted head type |
| **Combustion behaviour** | V0 (UL94) |
| **Tightening torque** | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| **Protection against electric shock** | Class II (IEC-EN61140) |
| **Heavy metal-free** | yes |
| **PVC-free** | yes |
| **Silicon-free** | yes |
| **Halogen-free** | yes |
| **Combustion behaviour** | 960°(IEC-EN60695-2-12) |
| **Fitted for outdoor application** | yes |
| **Pushbutton selection** | See 020 product range: 020 SM2 Command&Signalling; |
| **Warranty period** | 18 months |

## Disegni tecnici

