

## Datablad

080F0808-5F9T

Drukknopkast 84x84 met noodstopdrukknop rond Ø 90, trekontgrendeling, zwart



## Kenmerken

|                     |  |
|---------------------|--|
| <b>Bereik</b>       | Complete drukknoopkasten 84x84 mm  |
| <b>Component</b>    | Noodstopknop rond Ø 90, trekontgrendeling, met drukknoopkast                 |
| <b>Rubriek</b>      | 080F0808-5F9T  |
| <b>Omschrijving</b> | Drukknoopkast 84x84 met noodstopdrukknop rond Ø 90, trekontgrendeling, zwart |
| <b>Kleur</b>        | Grigio RAL7016 / Grigio RAL7035  |
| <b>Gewicht</b>      | 183,0  |
| <b>Douanetarief</b> | 85371098   |
| <b>GTIN</b>         | 8052878054748  |

## Technische gegevens

|  |   |
|--|---|
| <b>Approvals</b>                         | CE  |
| <b>Compliance with standards</b>         | IEC-ENC60947-1, IEC-EN60947-5-1               |
| <b>Compliance with standards</b>         | IEC-EN62208                                   |
| <b>Operating temperatures</b>            | -30° ÷ +70°C                                  |
| <b>Protection degree</b>                 | IP66 - IP69 (IEC-EN60529)                     |
| <b>Enclosure material</b>                | PA Polyamide                                  |
| <b>Gasket material</b>                   | TPE thermoplastic elastomer                   |
| <b>Screw material</b>                    | Stainless steel AISI 304                      |
| <b>Screw type</b>                        | Torx T15 slotted head type                    |
| <b>Combustion behaviour</b>              | V0 (UL94)                                     |
| <b>Tightening torque</b>                 | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)                   |
| <b>Protection against electric shock</b> | Class II (IEC-EN61140)                        |
| <b>Heavy metal-free</b>                  | yes   |
| <b>PVC-free</b>                          | yes   |
| <b>Silicon-free</b>                      | yes   |
| <b>Halogen-free</b>                      | yes   |
| <b>Combustion behaviour</b>              | 960°(IEC-EN60695-2-11)                        |
| <b>Fitted for outdoor application</b>    | yes   |
| <b>Pushbutton characteristics</b>        | See items 020PTF9MR-020PTF9MN-020GE10-020GE01 |

---

**Warranty period**

18 months

---

# Technische tekeningen

