

## Datasheet

080F0808-5GF5M

Push-button enclosure 84x84 with palm push-button Ø 50, big dome, red, momentary, yellow



## Features

<b>Range</b>	Emergency stop push-button enclosure 84x84 mm
<b>components</b>	Emergency push-button Ø 50, momentary, with enclosure
<b>Code</b>	080F0808-5GF5M
<b>Description</b>	Push-button enclosure 84x84 with palm push-button Ø 50, big dome, red, momentary, yellow
<b>Colour</b>	Giallo RAL1003 / Grigio RAL7035
<b>Weight - gr</b>	145.0
<b>Customs Tariff</b>	85371098
<b>GTIN</b>	8052878054298

## Datasheet

<b>Approvals</b>	CE
<b>Compliance with standards</b>	IEC-ENC60947-1, IEC-EN60947-5-1
<b>Compliance with standards</b>	IEC-EN62208
<b>Operating temperatures</b>	-30° ÷ +70°C
<b>Protection degree</b>	IP66 - IP69 (IEC-EN60529)
<b>Enclosure material</b>	PA Polyamide
<b>Gasket material</b>	TPE thermoplastic elastomer
<b>Screw material</b>	Stainless steel AISI 304
<b>Screw type</b>	Torx T15 slotted head type
<b>Combustion behaviour</b>	V0 (UL94)
<b>Tightening torque</b>	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Heavy metal-free</b>	yes
<b>PVC-free</b>	yes
<b>Silicon-free</b>	yes
<b>Halogen-free</b>	yes
<b>Combustion behaviour</b>	960°(IEC-EN60695-2-11)
<b>Fitted for outdoor application</b>	yes
<b>Pushbutton characteristics</b>	See items 020PTF5MR-020PTF5MN-020GE10-020GE01

---

**Warranty period**

18 months

---

# Technical drawings

