


Scheda Dati

080F0808-5GF5M

Drukknopkast 84x84 met noodstopdrukknop rond Ø 50, rood, tijdelijk, geel



Caratteristiche

Bereik	Noodstopkasten 84x84 mm
Componente	Noodstopknop Ø 50, tijdelijk, met drukknopkast
Rubriek	080F0808-5GF5M
Omschrijving	Drukknopkast 84x84 met noodstopdrukknop rond Ø 50, rood, tijdelijk, geel
Kleur	Giallo RAL1003 / Grigio RAL7035
Peso	145,0
Tariffa doganale	85371098
GTIN	8052878054298

Dati tecnici

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Compliance with standards	IEC-EN62208
Operating temperatures	-30° ÷ +70°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Enclosure material	PA Polyamide
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Tightening torque	0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Heavy metal-free	yes
PVC-free	yes
Silicon-free	yes
Halogen-free	yes
Combustion behaviour	HB (UL94)
Combustion behaviour	650°(IEC-EN60695-2-11)
Fitted for outdoor application	yes See items
Pushbutton characteristics	020PTF5MR-020PTF9MR-020PTF9PTR-020GE01
Warranty period	18 months

Disegni tecnici

