


## Scheda Dati

080F0808-5GF5T

Scatola pulsantiera 84x84 con pulsante a fungo sferico Ø 50, sgancio trazione, rosso



## Caratteristiche

<b>Gamma</b>	Scatole pulsantiere emergenza 84x84 mm
<b>Componente</b>	Pulsante di emergenza Ø 50, sgancio trazione, con scatola
<b>Codice</b>	080F0808-5GF5T
<b>Descrizione</b>	Scatola pulsantiera 84x84 con pulsante a fungo sferico
<b>Colore</b>	Giallo RAL1003 / Grigio RAL7035
<b>Peso</b>	145,0
<b>Tariffa doganale</b>	85371098
<b>GTIN</b>	8052878054304

## Dati tecnici

<b>Approvals</b>	CE
<b>Compliance with standards</b>	UNI EN ISO 13850, UNI EN ISO 12100, IEC-EN60947-5-5
<b>Compliance with standards</b>	IEC-ENC60947-1, IEC-EN60947-5-1
<b>Operating temperatures</b>	-30° ÷ +70°C
<b>Protection degree</b>	IP66 - IP69 (IEC-EN60529)
<b>Enclosure material</b>	PA Polyamide
<b>Gasket material</b>	TPE thermoplastic elastomer
<b>Screw material</b>	Stainless steel AISI 304
<b>Screw type</b>	Torx T15 slotted head type
<b>Combustion behaviour</b>	V0 (UL94)
<b>Tightening torque</b>	0.6 ÷ 0.8Nm (5.3 ÷ 7.1 Lb-in)
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Heavy metal-free</b>	yes
<b>PVC-free</b>	yes
<b>Silicon-free</b>	yes
<b>Halogen-free</b>	yes
<b>Combustion behaviour</b>	960°(IEC-EN60695-2-11)
<b>Fitted for outdoor application</b>	yes
<b>Pushbutton characteristics</b>	See items 020PTF5PTR-020GE01
<b>Warranty period</b>	18 months

## Disegni tecnici

