

Fiche technique

080F0808-5GF9T

Boîte à boutons 84x84 avec bouton-poussoir à paume Ø 90, déverrouillage par traction, rouge



Caractéristiques

Portée	Boîtes à boutons arrêt urgence 84x84 mm
Composant	B.P. d'urgence Ø 90, déverrouillage traction, avec boîte
Code	080F0808-5GF9T
Désignation des marchandises	Boîte à boutons 84x84 avec bouton-poussoir à paume Ø 90, déverrouillage par traction, rouge
Couleur	Giallo RAL1003 / Grigio RAL7035
Poids	183,0
Tarif douanier	85371098
GTIN	8052878054779

Données techniques

Approvals	CE
Compliance with standards	UNI EN ISO 13850, UNI EN ISO 12100, IEC-EN60947-5-5
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Operating temperatures	-30° ÷ +70°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Enclosure material	PA Polyamide
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Screw type	Torx T15 slotted head type
Combustion behaviour	V0 (UL94)
Tightening torque	0.6 ÷ 0.8Nm (5.3 ÷ 7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Heavy metal-free	yes
PVC-free	yes
Silicon-free	yes
Halogen-free	yes
Combustion behaviour	960°(IEC-EN60695-2-11)
Fitted for outdoor application	yes
Pushbutton characteristics	See items 020PTF9PTR-020GE01

Warranty period

18 months

Dessins techniques

