

Fiche technique

080F0808-5GFFA

Boîte à boutons 84x84 avec bouton-poussoir coup de poing, rouge Ø 60, déverrouillage par rotation, jaune



Caractéristiques

Portée	Boîtes à boutons arrêt urgence 84x84 mm
Composant	B.P. d'urgence Ø 60, déverrouillage rotation, avec boîte
Code	080F0808-5GFFA
Désignation des marchandises	Boîte à boutons 84x84 avec bouton-poussoir coup de poing, rouge Ø 60, déverrouillage par rotation, jaune
Couleur	Giallo RAL1003 / Grigio RAL7035
Poids	166,0
Tarif douanier	85371098
GTIN	8052878056605

Données techniques

Approvals	CE, UL, CSA, EAC
Compliance with standards	IEC-EN62208, UL508, CSA C22.2 No.14-13
Operating temperatures	-35° ÷ +80°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK07 (IEC-EN62262)
Enclosure material	PA Polyamide
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Heavy metal-free	yes
PVC-free	yes
Silicon-free	yes
Halogen-free	yes
Combustion behaviour	HB (UL94)
Combustion behaviour	650°(IEC-EN60695-2-11)
Fitted for outdoor application	yes
Warranty period	18 months

Dessins techniques

