

## Scheda Dati

080F0808-5P1

Painikepaneelikotelo 84x84, 1 aukko Ø 22



## Caratteristiche

Range	Painikekotelot 84x84 mm
Componente	Painikepaneelikotelo 1 aukolla
Code	080F0808-5P1
Kuvaus	Painikepaneelikotelo 84x84, 1 aukko Ø 22
Väriä	Grigio RAL7016 / Grigio RAL7035
Peso	125,0
Tariffa doganale	85381000
GT	8052878063764

## Dati tecnici

Approvals	CE
Compliance with standards	IEC-EN62208
Operating temperatures	-35° ÷ +80°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK07 (IEC-EN62262)
Enclosure material	PA Polyamide
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Tightening torque	0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Heavy metal-free	yes
PVC-free	yes
Silicon-free	yes
Halogen-free	yes
Combustion behaviour	HB (UL94)
Combustion behaviour	650°(IEC-EN60695-2-11)
Fitted for outdoor application	yes
Warranty period	18 months

## Disegni tecnici

