

Scheda Dati

080F0808-5P1

Doos knoppenbord 84x84, 1 gat Ø 22



Caratteristiche

| | |
|-------------------------|------------------------------------|
| Bereik | Drukknopkasten 84x84 mm |
| Componente | Doos knoppenbord met 1 gat |
| Rubriek | 080F0808-5P1 |
| Omschrijving | Doos knoppenbord 84x84, 1 gat Ø 22 |
| Kleur | Grigio RAL7016 / Grigio RAL7035 |
| Peso | 125,0 |
| Tariffa doganale | 85381000 |
| GTIN | 8052878063764 |

Dati tecnici

| | |
|--|------------------------------|
| Approvals | CE |
| Compliance with standards | IEC-EN62208 |
| Operating temperatures | -35° ÷ +80°C |
| Protection degree | IP66 - IP69 (IEC-EN60529) |
| Protection against impact | IK07 (IEC-EN62262) |
| Enclosure material | PA Polyamide |
| Gasket material | TPE thermoplastic elastomer |
| Screw material | Stainless steel AISI 304 |
| Tightening torque | 0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Heavy metal-free | yes |
| PVC-free | yes |
| Silicon-free | yes |
| Halogen-free | yes |
| Combustion behaviour | HB (UL94) |
| Combustion behaviour | 650°(IEC-EN60695-2-11) |
| Fitted for outdoor application | yes |
| Warranty period | 18 months |

Disegni tecnici

