

Datenblatt

080F0808-5PR

Bedienpult-Gehäuse 84x84 mit Drucktaster mit Schutzring, rot



Merkmale

| | |
|------------------------|--|
| Baureihe | Drucktaster-Gehäuse, komplett, 84x84 mm |
| Komponenten | Drucktaster mit Schutzabdeckung, rot, im Gehäuse |
| Artikel-Nr. | 080F0808-5PR |
| Beschreibung | Bedienpult-Gehäuse 84x84 mit Drucktaster mit Schutzring, rot |
| Farbe | Rosso |
| Gewicht - gr | 142,0 |
| Zolltarifnummer | 85371098 |
| GTIN | 8052878063702 |

Technische Daten

| | |
|--|--|
| Approvals | CE |
| Compliance with standards | IEC-ENC60947-1, IEC-EN60947-5-1 |
| Compliance with standards | IEC-EN62208 |
| Operating temperatures | -30° ÷ +70°C |
| Protection degree | IP66 - IP69 (IEC-EN60529) |
| Enclosure material | PA Polyamide |
| Gasket material | TPE thermoplastic elastomer |
| Screw material | Stainless steel AISI 304 |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Heavy metal-free | yes |
| PVC-free | yes |
| Silicon-free | yes |
| Halogen-free | yes |
| Combustion behaviour | HB (UL94) |
| Combustion behaviour | 650°(IEC-EN60695-2-11) |
| Fitted for outdoor application | yes |
| Pushbutton characteristics | See items 020PI*-020SMBN-020GE10/020GE01 |
| Warranty period | 18 months |

Technische Zeichnungen

