

Datasheet

080F0808-5PR

Push-button enclosure 84x84 with guarded push-button, red



Features

Range	Assembled push-button enclosures 84x84 mm
components	Guarded push-button, red, with enclosure
Code	080F0808-5PR
Description	Push-button enclosure 84x84 with guarded push-button, red
Colour	Rosso
Weight - gr	142.0
Customs Tariff	85371098
GTIN	8052878063702

Datasheet

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Compliance with standards	IEC-EN62208
Operating temperatures	-30° ÷ +70°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Enclosure material	PA Polyamide
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Heavy metal-free	yes
PVC-free	yes
Silicon-free	yes
Halogen-free	yes
Combustion behaviour	HB (UL94)
Combustion behaviour	650°(IEC-EN60695-2-11)
Fitted for outdoor application	yes
Pushbutton characteristics	See items 020PI*-020SMBN-020GE10/020GE01
Warranty period	18 months

Technical drawings

