

Datasheet

080F0808-5PR

Push-button enclosure 84x84 with guarded push-button, red



Features

| | |
|-----------------------|---|
| Range | Assembled push-button enclosures 84x84 mm |
| components | Guarded push-button, red, with enclosure |
| Code | 080F0808-5PR |
| Description | Push-button enclosure 84x84 with guarded push-button, red |
| Colour | Rosso |
| Weight - gr | 142.0 |
| Customs Tariff | 85371098 |
| GTIN | 8052878063702 |

Datasheet

| | |
|--|---|
| Approvals | CE |
| Compliance with standards | IEC-EN62208, UL508, CSA C22.2 No.14-13 |
| Compliance with standards | IEC-ENC60947-1, IEC-EN60947-5-1 |
| Operating temperatures | -30° ÷ +70°C |
| Protection degree | IP66 - IP69 (IEC-EN60529) |
| Enclosure material | PA Polyamide |
| Gasket material | TPE thermoplastic elastomer |
| Screw material | Stainless steel AISI 304 |
| Tightening torque | 0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Heavy metal-free | yes |
| PVC-free | yes |
| Silicon-free | yes |
| Halogen-free | yes |
| Combustion behaviour | HB (UL94) |
| Combustion behaviour | 650°(IEC-EN60695-2-11) |
| Fitted for outdoor application | yes |
| Pushbutton characteristics | See items 020PIN-020PIR-020SMAN-020GE10 |
| Warranty period | 18 months |

Technical drawings

