

## Datenblatt

080F0808-5SM

Bedienpult-Gehäuse 84x84 mit Drehknopf- Wahlschalter, 2 Positionen, schwarz



## Merkmale

|                        |   |
|------------------------|---|
| <b>Baureihe</b>        | Drucktaster-Gehäuse, komplett, 84x84 mm                                     |
| <b>Komponenten</b>     | Drehknopf-Wahlschalter, 2 Positionen, schwarz, im Gehäuse                   |
| <b>Artikel-Nr.</b>     | 080F0808-5SM  |
| <b>Beschreibung</b>    | Bedienpult-Gehäuse 84x84 mit Drehknopf- Wahlschalter, 2 Positionen, schwarz |
| <b>Farbe</b>           | Nero  |
| <b>Gewicht - gr</b>    | 150,0   |
| <b>Zolltarifnummer</b> | 85371098  |
| <b>GTIN</b>            | 8052878063733   |

## Technische Daten

|  |  |
|--|--|
| <b>Approvals</b>                         | CE                                       |
| <b>Compliance with standards</b>         | IEC-ENC60947-1, IEC-EN60947-5-1          |
| <b>Compliance with standards</b>         | IEC-EN62208                              |
| <b>Operating temperatures</b>            | -30° ÷ +70°C                             |
| <b>Protection degree</b>                 | IP66 - IP69 (IEC-EN60529)                |
| <b>Enclosure material</b>                | PA Polyamide                             |
| <b>Gasket material</b>                   | TPE thermoplastic elastomer              |
| <b>Screw material</b>                    | Stainless steel AISI 304                 |
| <b>Tightening torque</b>                 | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)              |
| <b>Protection against electric shock</b> | Class II (IEC-EN61140)                   |
| <b>Heavy metal-free</b>                  | yes                                      |
| <b>PVC-free</b>                          | yes                                      |
| <b>Silicon-free</b>                      | yes                                      |
| <b>Halogen-free</b>                      | yes                                      |
| <b>Combustion behaviour</b>              | HB (UL94)                                |
| <b>Combustion behaviour</b>              | 650°(IEC-EN60695-2-11)                   |
| <b>Fitted for outdoor application</b>    | yes                                      |
| <b>Pushbutton characteristics</b>        | See items 020PI*-020SMBN-020GE10/020GE01 |
| <b>Warranty period</b>                   | 18 months                                |

# Technische Zeichnungen

