

## Scheda Dati

080F0808-5SM

Painikekotelo 84x84, 2-asentoisella vääntökytkimellä, musta



## Caratteristiche

<b>Range</b>	Täydelliset painikekotelot 84x84 mm
<b>Componente</b>	Vääntökytkin, musta, 2-asentoinen, kanssa kotelo
<b>Code</b>	080F0808-5SM
<b>Kuvaus</b>	Painikekotelo 84x84, 2-asentoisella vääntökytkimellä, musta
<b>Väriä</b>	Nero
<b>Peso</b>	150,0
<b>Tariffa doganale</b>	85371098
<b>GT</b>	8052878063733

## Dati tecnici

<b>Approvals</b>	CE
<b>Compliance with standards</b>	IEC-EN62208, UL508, CSA C22.2 No.14-13
<b>Compliance with standards</b>	IEC-ENC60947-1, IEC-EN60947-5-1
<b>Operating temperatures</b>	-30° ÷ +70°C
<b>Protection degree</b>	IP66 - IP69 (IEC-EN60529)
<b>Enclosure material</b>	PA Polyamide
<b>Gasket material</b>	TPE thermoplastic elastomer
<b>Screw material</b>	Stainless steel AISI 304
<b>Tightening torque</b>	0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in)
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Heavy metal-free</b>	yes
<b>PVC-free</b>	yes
<b>Silicon-free</b>	yes
<b>Halogen-free</b>	yes
<b>Combustion behaviour</b>	HB (UL94)
<b>Combustion behaviour</b>	650°(IEC-EN60695-2-11)
<b>Fitted for outdoor application</b>	yes
<b>Pushbutton characteristics</b>	See items 020PIN-020PIR-020SMAN-020GE10
<b>Warranty period</b>	18 months

## Disegni tecnici

