

Datablad

080F0808-8GF4AP

Drukknopkast 84x84 met bescherming e noodstopdrukknop Ø 40, rood, draaiontgrendeling, geel



Kenmerken

Bereik	Noodstopkasten 84x84 mm
Component	Noodstopknop Ø 40, draaiontgrendeling, met drukknoopkast
Rubriek	080F0808-8GF4AP
Omschrijving	Drukknoopkast 84x84 met bescherming e noodstopdrukknop Ø 40, rood, draaiontgrendeling, geel
Kleur	Giallo RAL1003 / Grigio RAL7035
Gewicht	165,0
Douanetarief	85371098
GTIN	8052878063276

Technische gegevens

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Compliance with standards	IEC-EN62208
Operating temperatures	-30° ÷ +70°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK05 (IEC-EN62262)
Enclosure material	PA Polyamide
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Heavy metal-free	yes
PVC-free	yes
Silicon-free	yes
Halogen-free	yes
Combustion behaviour	HB (UL94)
Combustion behaviour	650°(IEC-EN60695-2-11)
Fitted for outdoor application	yes
Pushbutton characteristics	See items 020PTFAR - 020GE01

Warranty period

18 months

Technische tekeningen

