

Scheda Dati

080F0808-8GF4AP  
Caixa botoeira 84x84 com proteção e botão cogumelo Ø 40, vermelho, desengate rotação, amarelo



Caratteristiche

|                  |                                                                                               |
|------------------|-----------------------------------------------------------------------------------------------|
| Gama             | Caixas botoeiras parada emergência 84x84 mm                                                   |
| Componente       | Botão de emergência Ø 40, desengate rotação, com caixa                                        |
| Código           | 080F0808-8GF4AP                                                                               |
| Descrição        | Caixa botoeira 84x84 com proteção e botão cogumelo Ø 40, vermelho, desengate rotação, amarelo |
| Cor              | Giallo RAL1003 / Grigio RAL7035                                                               |
| Peso             | 165,0                                                                                         |
| Tariffa doganale | 85371098                                                                                      |
| GTIN             | 8052878063276                                                                                 |

Dati tecnici

|                                   |                                 |
|-----------------------------------|---------------------------------|
| Approvals                         | CE                              |
| Compliance with standards         | IEC-ENC60947-1, IEC-EN60947-5-1 |
| Compliance with standards         | IEC-EN62208                     |
| Operating temperatures            | -30° ÷ +70°C                    |
| Protection degree                 | IP66 - IP69 (IEC-EN60529)       |
| Protection against impact         | IK05 (IEC-EN62262)              |
| Enclosure material                | PA Polyamide                    |
| Gasket material                   | TPE thermoplastic elastomer     |
| Screw material                    | Stainless steel AISI 304        |
| Tightening torque                 | 0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in)    |
| Protection against electric shock | Class II (IEC-EN61140)          |
| Heavy metal-free                  | yes                             |
| PVC-free                          | yes                             |
| Silicon-free                      | yes                             |
| Halogen-free                      | yes                             |
| Combustion behaviour              | HB (UL94)                       |
| Combustion behaviour              | 650°(IEC-EN60695-2-11)          |
| Fitted for outdoor application    | yes                             |
| Pushbutton characteristics        | See items 020PTFAR - 020GE01    |

Warranty period

18 months

Disegni tecnici

