

## Scheda Dati

080F0808-F9M

Uppoasennettu painikekotelo 84x84 hätä-/seis- kämmenpainikkella Ø 90, väliaikainen, musta



## Caratteristiche

|                  |                                                                                          |
|------------------|------------------------------------------------------------------------------------------|
| Range            | Täydelliset painikekotelot 84x84 mm                                                      |
| Componente       | Hätä-/seis painike Ø 90, väliaikainen, uppoasennettu                                     |
| Code             | 080F0808-F9M                                                                             |
| Kuvaus           | Uppoasennettu painikekotelo 84x84 hätä-/seis-kämmenpainikkella Ø 90, väliaikainen, musta |
| Väriä            | Nero                                                                                     |
| Peso             | 102,0                                                                                    |
| Tariffa doganale | 85371098                                                                                 |
| GT               | 8052878063351                                                                            |

## Dati tecnici

|                                   |                                        |
|-----------------------------------|----------------------------------------|
| Approvals                         | CE                                     |
| Compliance with standards         | IEC-EN62208, UL508, CSA C22.2 No.14-13 |
| Compliance with standards         | IEC-ENC60947-1, IEC-EN60947-5-1        |
| Operating temperatures            | -30° ÷ +70°C                           |
| Protection degree                 | IP66 - IP69 (IEC-EN60529)              |
| Enclosure material                | PA Polyamide                           |
| Gasket material                   | TPE thermoplastic elastomer            |
| Screw material                    | Stainless steel AISI 304               |
| Tightening torque                 | 0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in)           |
| Protection against electric shock | Class II (IEC-EN61140)                 |
| Heavy metal-free                  | yes                                    |
| PVC-free                          | yes                                    |
| Silicon-free                      | yes                                    |
| Halogen-free                      | yes                                    |
| Combustion behaviour              | HB (UL94)                              |
| Combustion behaviour              | 650°(IEC-EN60695-2-11)                 |
| Fitted for outdoor application    | yes                                    |
| Pushbutton characteristics        | See items 020PTF9MN-020PTF9PTN-020GE10 |
| Warranty period                   | 18 months                              |

Disegni tecnici

