

Fiche technique

080F0808-GF4AP

Bouton-poussoir pour arrêt d'urgence à encastrer 84x84, coup de poing avec garde Ø 40, déverrouillage rotation, rouge



Caractéristiques

Portée	Boîtes à boutons arrêt urgence 84x84 mm
Composant	B.P. d'urgence Ø 40, déverrouillage rotation, à encastrer
Code	080F0808-GF4AP
Désignation des marchandises	Bouton-poussoir pour arrêt d'urgence à encastrer 84x84, coup de poing avec garde Ø 40, déverrouillage rotation, rouge
Couleur	Rosso
Poids	110,0
Tarif douanier	85371098
GTIN	8052878064075

Données techniques

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Compliance with standards	IEC-EN62208
Operating temperatures	-30° ÷ +70°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK05 (IEC-EN62262)
Enclosure material	PA Polyamide
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Heavy metal-free	yes
PVC-free	yes
Silicon-free	yes
Halogen-free	yes
Combustion behaviour	HB (UL94)
Combustion behaviour	650°(IEC-EN60695-2-11)
Fitted for outdoor application	yes
Pushbutton characteristics	See items 020PTFAR - 020GE01

Warranty period

18 months

Dessins techniques

