

## Scheda Dati

080F0808-GF4AP

Pulsante di emergenza ad incasso 84x84, pulsante a fungo protetto Ø 40, rosso, sgancio rotazione



## Caratteristiche

<b>Gamma</b>	Scatole pulsantiere emergenza 84x84 mm
<b>Componente</b>	Pulsante di emergenza Ø 40, sgancio rotazione, ad incasso
<b>Codice</b>	080F0808-GF4AP
<b>Descrizione</b>	Pulsante di emergenza ad incasso 84x84, pulsante a fungo
<b>Colore</b>	Rosso
<b>Peso</b>	110,0
<b>Tariffa doganale</b>	85371098
<b>GTIN</b>	8052878064075

## Dati tecnici

<b>Approvals</b>	CE
<b>Compliance with standards</b>	IEC-ENC60947-1, IEC-EN60947-5-1
<b>Compliance with standards</b>	IEC-EN62208
<b>Operating temperatures</b>	-30° ÷ +70°C
<b>Protection degree</b>	IP66 - IP69 (IEC-EN60529)
<b>Protection against impact</b>	IK05 (IEC-EN62262)
<b>Enclosure material</b>	PA Polyamide
<b>Gasket material</b>	TPE thermoplastic elastomer
<b>Screw material</b>	Stainless steel AISI 304
<b>Tightening torque</b>	0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in)
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Heavy metal-free</b>	yes
<b>PVC-free</b>	yes
<b>Silicon-free</b>	yes
<b>Halogen-free</b>	yes
<b>Combustion behaviour</b>	HB (UL94)
<b>Combustion behaviour</b>	650°(IEC-EN60695-2-11)
<b>Fitted for outdoor application</b>	yes
<b>Pushbutton characteristics</b>	See items 020PTFAR - 020GE01
<b>Warranty period</b>	18 months

## Disegni tecnici

