

Datasheet

080F0808-GF5M

Wall-mounting emergency stop push-button 84x84, palm push-button Ø 50, big dome, momentary, red



Features

Range	Emergency stop push-button enclosure 84x84 mm
components	Emergency push-button Ø 50, momentary, wall-mounting
Code	080F0808-GF5M
Description	Wall-mounting emergency stop push-button 84x84, palm push-button Ø 50, big dome, momentary, red
Colour	Rosso
Weight - gr	84.0
Customs Tariff	85371098
GTIN	8052878063313

Datasheet

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Compliance with standards	IEC-EN62208
Operating temperatures	-30° ÷ +70°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Enclosure material	PA Polyamide
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Screw type	Torx T15 slotted head type
Combustion behaviour	V0 (UL94)
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Heavy metal-free	yes
PVC-free	yes
Silicon-free	yes
Halogen-free	yes
Combustion behaviour	960°(IEC-EN60695-2-11)
Fitted for outdoor application	yes
Pushbutton characteristics	See items 020PTF5MR-020PTF5MN-020GE10-020GE01

Warranty period

18 months

Technical drawings

