

Datablad

080F0808-GF5M

Inbouwmontage noodstopknop 84x84, noodstopknop rond Ø 50, tijdelijk, rood



Kenmerken

Bereik	Noodstopkasten 84x84 mm
Component	Noodstopknop rond Ø 50, tijdelijk, inbouwmontage
Rubriek	080F0808-GF5M
Omschrijving	Inbouwmontage noodstopknop 84x84, noodstopknop rond Ø 50, tijdelijk, rood
Kleur	Rosso
Gewicht	84,0
Douanetarief	85371098
GTIN	8052878063313

Technische gegevens

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Compliance with standards	IEC-EN62208
Operating temperatures	-30° ÷ +70°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Enclosure material	PA Polyamide
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Screw type	Torx T15 slotted head type
Combustion behaviour	V0 (UL94)
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Heavy metal-free	yes
PVC-free	yes
Silicon-free	yes
Halogen-free	yes
Combustion behaviour	960°(IEC-EN60695-2-11)
Fitted for outdoor application	yes
Pushbutton characteristics	See items 020PTF5MR-020PTF5MN-020GE10-020GE01
Warranty period	18 months

Technische tekeningen

