

## Datablad

080F0808-GF5M

Inbouwmontage noodstopknop 84x84, noodstopknop rond Ø 50, tijdelijk, rood



## Kenmerken

<b>Bereik</b>	Noodstopkasten 84x84 mm
<b>Component</b>	Noodstopknop rond Ø 50, tijdelijk, inbouwmontage
<b>Rubriek</b>	080F0808-GF5M
<b>Omschrijving</b>	Inbouwmontage noodstopknop 84x84, noodstopknop rond Ø 50, tijdelijk, rood
<b>Kleur</b>	Rosso
<b>Gewicht</b>	84,0
<b>Douanetarief</b>	85371098
<b>GTIN</b>	8052878063313

## Technische gegevens

<b>Approvals</b>	CE
<b>Compliance with standards</b>	IEC-ENC60947-1, IEC-EN60947-5-1
<b>Compliance with standards</b>	IEC-EN62208
<b>Operating temperatures</b>	-30° ÷ +70°C
<b>Protection degree</b>	IP66 - IP69 (IEC-EN60529)
<b>Enclosure material</b>	PA Polyamide
<b>Gasket material</b>	TPE thermoplastic elastomer
<b>Screw material</b>	Stainless steel AISI 304
<b>Screw type</b>	Torx T15 slotted head type
<b>Combustion behaviour</b>	V0 (UL94)
<b>Tightening torque</b>	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Heavy metal-free</b>	yes
<b>PVC-free</b>	yes
<b>Silicon-free</b>	yes
<b>Halogen-free</b>	yes
<b>Combustion behaviour</b>	960°(IEC-EN60695-2-11)
<b>Fitted for outdoor application</b>	yes
<b>Pushbutton characteristics</b>	See items 020PTF5MR-020PTF5MN-020GE10-020GE01
<b>Warranty period</b>	18 months

# Technische tekeningen

