

Hoja de datos

080F0808-GF5T

Pulsador de emergencia de empotrar 84x84, pulsador fungiforme esférico Ø 50, desenganche tracción, rojo



Características

Rango	Cajas botoneras pulsador emergencia 84x84 mm
Componente	Pulsador de emergencia Ø 50, desenganche tracción, de empotrar
Código	080F0808-GF5T
Descripción	Pulsador de emergencia de empotrar 84x84, pulsador fungiforme esférico Ø 50, desenganche tracción, rojo
Color	Rosso
Peso	84,0
Arancel aduanero	85371098
GTIN	8052878063320

Datos técnicos

Approvals	CE
Compliance with standards	UNI EN ISO 13850, UNI EN ISO 12100, IEC-EN60947-5-5
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Operating temperatures	-30° ÷ +70°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Enclosure material	PA Polyamide
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Screw type	Torx T15 slotted head type
Combustion behaviour	V0 (UL94)
Tightening torque	0.6 ÷ 0.8Nm (5.3 ÷ 7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Heavy metal-free	yes
PVC-free	yes
Silicon-free	yes
Halogen-free	yes
Combustion behaviour	960° (IEC-EN60695-2-11)
Fitted for outdoor application	yes
Pushbutton characteristics	See items 020PTF5PTR-020GE01

Warranty period

18 months

Dibujos técnicos

