

Datablad

080F0808-GF5T

Inbouwmontage noodstopknop 84x84, noodstopknop rond Ø 50, tractie ontgrendeling, rood



Kenmerken

| | |
|---------------------|---------------------------------------------------------------------------------------|
| Bereik | Noodstopkasten 84x84 mm |
| Component | Noodstopknop rond Ø 50, trekontgrendeling, inbouwmontage |
| Rubriek | 080F0808-GF5T |
| Omschrijving | Inbouwmontage noodstopknop 84x84, noodstopknop rond Ø 50, tractie ontgrendeling, rood |
| Kleur | Rosso |
| Gewicht | 84,0 |
| Douanetarief | 85371098 |
| GTIN | 8052878063320 |

Technische gegevens

| | |
|------------------------------------------|---------------------------------------------------|
| Approvals | CE |
| Compliance with standards | UNI EN ISO 13850,UNI EN ISO 12100,IEC-EN60947-5-5 |
| Compliance with standards | IEC-ENC60947-1, IEC-EN60947-5-1 |
| Operating temperatures | -30° ÷ +70°C |
| Protection degree | IP66 - IP69 (IEC-EN60529) |
| Enclosure material | PA Polyamide |
| Gasket material | TPE thermoplastic elastomer |
| Screw material | Stainless steel AISI 304 |
| Screw type | Torx T15 slotted head type |
| Combustion behaviour | V0 (UL94) |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Heavy metal-free | yes |
| PVC-free | yes |
| Silicon-free | yes |
| Halogen-free | yes |
| Combustion behaviour | 960°(IEC-EN60695-2-11) |
| Fitted for outdoor application | yes |
| Pushbutton characteristics | See items 020PTF5PTR-020GE01 |

Warranty period

18 months

Technische tekeningen

