

Scheda Dati

080F0808-GF9M

Bouton-poussoir pour arrêt d'urgence à encastrer 84x84, paume Ø 90, momentané, rouge



Caratteristiche

Portée	Boîtes à boutons arrêt urgence 84x84 mm
Componente	B.P. d'urgence Ø 90, momentané, à encastrer
Code	080F0808-GF9M
Désignation des marchandises	Bouton-poussoir pour arrêt d'urgence à encastrer 84x84, paume Ø 90, momentané, rouge
Couleur	Rosso
Peso	102,0
Tariffa doganale	85371098
GTIN	8052878063375

Dati tecnici

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Compliance with standards	IEC-EN62208
Operating temperatures	-30° ÷ +70°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Enclosure material	PA Polyamide
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Tightening torque	0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Heavy metal-free	yes
PVC-free	yes
Silicon-free	yes
Halogen-free	yes
Combustion behaviour	HB (UL94)
Combustion behaviour	650°(IEC-EN60695-2-11)
Fitted for outdoor application	yes
Pushbutton characteristics	See items 020PTF5MR-020PTF9MR-020PTF9PTR-020GE01
Warranty period	18 months

Disegni tecnici

