

## Datablad

080F0808-GP1

Inbouwmontage beugel voor drukknoppen 84x84, 1 gat Ø 22, geel



## Kenmerken

<b>Bereik</b>	Drukknopkasten 84x84 mm
<b>Component</b>	Geel deksel met 1 gat Ø 22
<b>Rubriek</b>	080F0808-GP1
<b>Omschrijving</b>	Inbouwmontage beugel voor drukknoppen 84x84, 1 gat Ø 22, geel
<b>Kleur</b>	Giallo
<b>Gewicht</b>	46,0
<b>Douanetarief</b>	85381000
<b>GTIN</b>	8052878063795

## Technische gegevens

<b>Approvals</b>	CE, UL, CSA, EAC
<b>Compliance with standards</b>	IEC-EN62208, UL508, CSA C22.2 No.14-13
<b>Operating temperatures</b>	-35° ÷ +80°C
<b>Protection degree</b>	IP66 - IP69 (IEC-EN60529)
<b>Protection against impact</b>	IK07 (IEC-EN62262)
<b>Enclosure material</b>	PA Polyamide
<b>Gasket material</b>	TPE thermoplastic elastomer
<b>Screw material</b>	Stainless steel AISI 304
<b>Tightening torque</b>	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Heavy metal-free</b>	yes
<b>PVC-free</b>	yes
<b>Silicon-free</b>	yes
<b>Halogen-free</b>	yes
<b>Combustion behaviour</b>	HB (UL94)
<b>Combustion behaviour</b>	650°(IEC-EN60695-2-11)
<b>Fitted for outdoor application</b>	yes
<b>Warranty period</b>	18 months

## Technische tekeningen

