

Datasheet

080F0808-P1

Wall-mounting support for push-button 84x84, 1 hole Ø 22



Features

| | |
|-----------------------|--|
| Range | Push-button enclosures 84x84 mm |
| components | 1-hole lid Ø 22 |
| Code | 080F0808-P1 |
| Description | Wall-mounting support for push-button 84x84, 1 hole Ø 22 |
| Colour | Grigio RAL7016 |
| Weight - gr | 46.0 |
| Customs Tariff | 85381000 |
| GTIN | 8052878063788 |

Datasheet

| | |
|--|--|
| Approvals | CE, UL, CSA, EAC |
| Compliance with standards | IEC-EN62208, UL508, CSA C22.2 No.14-13 |
| Operating temperatures | -35° ÷ +80°C |
| Protection degree | IP66 - IP69 (IEC-EN60529) |
| Protection against impact | IK07 (IEC-EN62262) |
| Enclosure material | PA Polyamide |
| Gasket material | TPE thermoplastic elastomer |
| Screw material | Stainless steel AISI 304 |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Heavy metal-free | yes |
| PVC-free | yes |
| Silicon-free | yes |
| Halogen-free | yes |
| Combustion behaviour | HB (UL94) |
| Combustion behaviour | 650°(IEC-EN60695-2-11) |
| Fitted for outdoor application | yes |
| Warranty period | 18 months |

Technical drawings

