# Datasheet

080F0808-PV
Wall-mounting guarded push-button 84x84, Ø 22, green





## Features

| | |
|---|---|
| **Range** | Assembled push-button enclosures 84x84 mm |
| **components** | Guarded push-button, green, wall-mounting |
| **Code** | 080F0808-PV |
| **Description** | Wall-mounting guarded push-button 84x84, Ø 22, green |
| **Colour** | Verde |
| **Weight - gr** | 72.0 |
| **Customs Tariff** | 85371098 |
| **GTIN** | 8052878063719 |

## Datasheet

| | |
|---|---|
| **Approvals** | CE |
| **Compliance with standards** | IEC-ENC60947-1, IEC-EN60947-5-1 |
| **Compliance with standards** | IEC-EN62208 |
| **Operating temperatures** | -30° ÷ +70°C |
| **Protection degree** | IP66 - IP69 (IEC-EN60529) |
| **Enclosure material** | PA Polyamide |
| **Gasket material** | TPE thermoplastic elastomer |
| **Screw material** | Stainless steel AISI 304 |
| **Tightening torque** | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| **Protection against electric shock** | Class II (IEC-EN61140) |
| **Heavy metal-free** | yes |
| **PVC-free** | yes |
| **Silicon-free** | yes |
| **Halogen-free** | yes |
| **Combustion behaviour** | HB (UL94) |
| **Combustion behaviour** | 650°(IEC-EN60695-2-12) |
| **Fitted for outdoor application** | yes |
| **Pushbutton characteristics** | See items 020PI*-020SMBN-020GE10/020GE01 |
| **Warranty period** | 18 months |

## Technical drawings




