

Scheda Dati

080F0808-SM

Uppoasennettu painikekotelo 84x84, 2-asentoisella vääntökytkimellä, musta



Caratteristiche

Range	Täydelliset painikekotelot 84x84 mm
Componente	Vääntökytkin, musta, 2-asentoinen, uppoasennettu
Code	080F0808-SM
Kuvaus	Uppoasennettu painikekotelo 84x84, 2-asentoisella vääntökytkimellä, musta
Väriä	Nero
Peso	80,0
Tariffa doganale	85371098
GT	8052878063740

Dati tecnici

Approvals	CE
Compliance with standards	IEC-EN62208, UL508, CSA C22.2 No.14-13
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Operating temperatures	-30° ÷ +70°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Enclosure material	PA Polyamide
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Tightening torque	0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Heavy metal-free	yes
PVC-free	yes
Silicon-free	yes
Halogen-free	yes
Combustion behaviour	HB (UL94)
Combustion behaviour	650°(IEC-EN60695-2-11)
Fitted for outdoor application	yes
Pushbutton characteristics	See items 020PIN-020PIR-020SMAN-020GE10
Warranty period	18 months

Disegni tecnici

