

Fiche technique

080F0808-SM

Bouton tournant à manette à encastrer 84x84, Ø 22, à 2 positions, noir



Caractéristiques

| | |
|-------------------------------------|--|
| Portée | Boîtes à boutons complètes 84x84 mm |
| Composant | Bouton tournant à manette à 2 positions, noir, à encastrer |
| Code | 080F0808-SM |
| Désignation des marchandises | Bouton tournant à manette à encastrer 84x84, Ø 22, à 2 positions, noir |
| Couleur | Nero |
| Poids | 80,0 |
| Tarif douanier | 85371098 |
| GTIN | 8052878063740 |

Données techniques

| | |
|--|--|
| Approvals | CE |
| Compliance with standards | IEC-ENC60947-1, IEC-EN60947-5-1 |
| Compliance with standards | IEC-EN62208 |
| Operating temperatures | -30° ÷ +70°C |
| Protection degree | IP66 - IP69 (IEC-EN60529) |
| Enclosure material | PA Polyamide |
| Gasket material | TPE thermoplastic elastomer |
| Screw material | Stainless steel AISI 304 |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Heavy metal-free | yes |
| PVC-free | yes |
| Silicon-free | yes |
| Halogen-free | yes |
| Combustion behaviour | HB (UL94) |
| Combustion behaviour | 650°(IEC-EN60695-2-11) |
| Fitted for outdoor application | yes |
| Pushbutton characteristics | See items 020PI*-020SMBN-020GE10/020GE01 |
| Warranty period | 18 months |

Dessins techniques

