

## Scheda Dati

080R140-G

Hangende drukknopkast, afstandsbediening, zonder gaten, geel



## Caratteristiche

|                         |                                                              |
|-------------------------|--------------------------------------------------------------|
| <b>Bereik</b>           | Hangende drukknopkasten, afstandsbediening 140x83 mm         |
| <b>Componente</b>       | Zonder gaten                                                 |
| <b>Rubriek</b>          | 080R140-G                                                    |
| <b>Omschrijving</b>     | Hangende drukknopkast, afstandsbediening, zonder gaten, geel |
| <b>Kleur</b>            | Giallo RAL1003 / Grigio RAL7035                              |
| <b>Peso</b>             | 160,0                                                        |
| <b>Tariffa doganale</b> | 85381000                                                     |
| <b>GTIN</b>             | 8052878066093                                                |

## Dati tecnici

|                                                 |                                                |
|-------------------------------------------------|------------------------------------------------|
| <b>Approvals</b>                                | CE                                             |
| <b>Compliance with standards</b>                | IEC-ENC60947-1, IEC-EN60947-5-1, IEC-EN60204-1 |
| <b>Operating temperatures</b>                   | -35° ÷ +80°C                                   |
| <b>Protection degree</b>                        | IP66 - IP69 (IEC-EN60529)                      |
| <b>Protection against impact</b>                | IK08 (IEC-EN62262)                             |
| <b>Housing material</b>                         | High impact grade thermoplastic polymer        |
| <b>Manufacturing process</b>                    | Injection moulding                             |
| <b>Gasket material</b>                          | TPE thermoplastic elastomer                    |
| <b>Screw material</b>                           | Stainless steel AISI 304                       |
| <b>Screw type</b>                               | Torx T15 slotted head type                     |
| <b>Tightening torque</b>                        | 0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in)                   |
| <b>Cable clamp screw</b>                        | Tightening torque 1.5Nm (13.3 Lb-in) max.      |
| <b>Pendant fixing ring</b>                      | Stainless steel AISI 304                       |
| <b>Flexible cable gland</b>                     | M16x1.5 suitable for cable D.5÷10mm            |
| <b>Rated insulation voltage</b>                 | Ui 300V - Uimp 2.5KV (IEC-EN60947-1)           |
| <b>Protection against electric shock</b>        | Class II (IEC-EN61140)                         |
| <b>Combustion behaviour</b>                     | HB (UL94)                                      |
| <b>Combustion behaviour</b>                     | 650°(IEC-EN60695-2-11)                         |
| <b>Fitted for outdoor application</b>           | yes                                            |
| <b>Pushbutton and electrical contacts block</b> | See 020 product range: 020 SM2 D.22mm          |

---

**Warranty period**

18 months

---

## Disegni tecnici

