

Hoja de datos

080R140-GP2

Estación de control colgante, control remoto, 2 orificios, amarillo



Características

Rango	Estaciones de control colgantes, control remoto 140x83 mm
Componente	Con 2 orificios Ø 22
Código	080R140-GP2
Descripción	Estación de control colgante, control remoto, 2 orificios, amarillo
Color	Giallo RAL1003 / Grigio RAL7035
Peso	208,0
Arancel aduanero	85381000
GTIN	8052878066147

Datos técnicos

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1, IEC-EN60204-1
Operating temperatures	-35° ÷ +80°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK08 (IEC-EN62262)
Housing material	High impact grade thermoplastic polymer
Manufacturing process	Injection moulding
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Screw type	Torx T15 slotted head type
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Cable clamp screw	Tightening torque 1.5Nm (13.3 Lb-in) max.
Pendant fixing ring	Stainless steel AISI 304
Flexible cable gland	M16x1.5 suitable for cable D.5÷10mm
Rated insulation voltage	Ui 300V - Uimp 2.5KV (IEC-EN60947-1)
Protection against electric shock	Class II (IEC-EN61140)
Combustion behaviour	HB (UL94)
Combustion behaviour	650°(IEC-EN60695-2-11)
Fitted for outdoor application	yes
Pushbutton and electrical contacts block	See 020 product range: 020 SM2 D.22mm

Warranty period

18 months

Dibujos técnicos

