

Scheda Dati

080R140-GP2

Riippuhjain, kaukosäädin, 2 aukolla, keltainen



Caratteristiche

| | |
|-------------------------|--|
| Gamma | Riippuhjainyksikkö, kaukosäädin 140x83 mm |
| Componente | 2 aukolla Ø 22 |
| Codice | 080R140-GP2 |
| Descrizione | Riippuhjain, kaukosäädin, 2 aukolla, keltainen |
| Colore | Giallo RAL1003 / Grigio RAL7035 |
| Peso | 208,0 |
| Tariffa doganale | 85381000 |
| GTIN | 8052878066147 |

Dati tecnici

| | |
|---|--|
| Approvals | CE |
| Compliance with standards | IEC-ENC60947-1, IEC-EN60947-5-1, IEC-EN60204-1 |
| Operating temperatures | -35° ÷ +80°C |
| Protection degree | IP66 - IP69 (IEC-EN60529) |
| Protection against impact | IK08 (IEC-EN62262) |
| Housing material | High impact grade thermoplastic polymer |
| Manufacturing process | Injection moulding |
| Gasket material | TPE thermoplastic elastomer |
| Screw material | Stainless steel AISI 304 |
| Screw type | Torx T15 slotted head type |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Cable clamp screw | Tightening torque 1.5Nm (13.3 Lb-in) max. |
| Pendant fixing ring | Stainless steel AISI 304 |
| Flexible cable gland | M16x1.5 suitable for cable D.5÷10mm |
| Rated insulation voltage | Ui 300V - Uimp 2.5KV (IEC-EN60947-1) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Combustion behaviour | HB (UL94) |
| Combustion behaviour | 650°(IEC-EN60695-2-11) |
| Fitted for outdoor application | yes |
| Pushbutton and electrical contacts block | See 020 product range: 020 SM2 D.22mm |
| Warranty period | 18 months |

Disegni tecnici

