

Datablad

080R140-GP2

Hangende drukknopkast, afstandsbediening, 2 gaten, geel



Kenmerken

Bereik	Hangende drukknopkasten, afstandsbediening 140x83 mm
Component	Met 2 gaten Ø 22
Rubriek	080R140-GP2
Omschrijving	Hangende drukknopkast, afstandsbediening, 2 gaten, geel
Kleur	Giallo RAL1003 / Grigio RAL7035
Gewicht	208,0
Douanetarief	85381000
GTIN	8052878066147

Technische gegevens

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1, IEC-EN60204-1
Operating temperatures	-35° ÷ +80°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK08 (IEC-EN62262)
Housing material	High impact grade thermoplastic polymer
Manufacturing process	Injection moulding
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Screw type	Torx T15 slotted head type
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Cable clamp screw	Tightening torque 1.5Nm (13.3 Lb-in) max.
Pendant fixing ring	Stainless steel AISI 304
Flexible cable gland	M16x1.5 suitable for cable D.5÷10mm
Rated insulation voltage	Ui 300V - Uimp 2.5KV (IEC-EN60947-1)
Protection against electric shock	Class II (IEC-EN61140)
Combustion behaviour	HB (UL94)
Combustion behaviour	650°(IEC-EN60695-2-11)
Fitted for outdoor application	yes
Pushbutton and electrical contacts block	See 020 product range: 020 SM2 D.22mm
Warranty period	18 months

Technische tekeningen

