

## Datasheet

080R140-P1

Pendant push-button station, remote control, 1 hole, grey



## Features

|                       |   |
|-----------------------|---|
| <b>Range</b>          | Pendant push-button stations, remote control 140x83 mm    |
| <b>components</b>     | With 1 hole Ø 22  |
| <b>Code</b>           | 080R140-P1  |
| <b>Description</b>    | Pendant push-button station, remote control, 1 hole, grey |
| <b>Colour</b>         | Grigio RAL7016 / Grigio RAL7035                           |
| <b>Weight - gr</b>    | 210.0   |
| <b>Customs Tariff</b> | 85381000  |
| <b>GTIN</b>           | 8052878066109   |

## Datasheet

|   |  |
|---|--|
| <b>Approvals</b>                                | CE   |
| <b>Compliance with standards</b>                | IEC-ENC60947-1, IEC-EN60947-5-1, IEC-EN60204-1 |
| <b>Operating temperatures</b>                   | -35° ÷ +80°C                                   |
| <b>Protection degree</b>                        | IP66 - IP69 (IEC-EN60529)                      |
| <b>Protection against impact</b>                | IK08 (IEC-EN62262)                             |
| <b>Housing material</b>                         | High impact grade thermoplastic polymer        |
| <b>Manufacturing process</b>                    | Injection moulding                             |
| <b>Gasket material</b>                          | TPE thermoplastic elastomer                    |
| <b>Screw material</b>                           | Stainless steel AISI 304                       |
| <b>Screw type</b>                               | Torx T15 slotted head type                     |
| <b>Tightening torque</b>                        | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)                    |
| <b>Cable clamp screw</b>                        | Tightening torque 1.5Nm (13.3 Lb-in) max.      |
| <b>Pendant fixing ring</b>                      | Stainless steel AISI 304                       |
| <b>Flexible cable gland</b>                     | M16x1.5 suitable for cable D.5÷10mm            |
| <b>Rated insulation voltage</b>                 | Ui 300V - Uimp 2.5KV (IEC-EN60947-1)           |
| <b>Protection against electric shock</b>        | Class II (IEC-EN61140)                         |
| <b>Combustion behaviour</b>                     | HB (UL94)                                      |
| <b>Combustion behaviour</b>                     | 650°(IEC-EN60695-2-11)                         |
| <b>Fitted for outdoor application</b>           | yes  |
| <b>Pushbutton and electrical contacts block</b> | See 020 product range: 020 SM2 D.22mm          |
| <b>Warranty period</b>                          | 18 months                                      |

## Technical drawings

