

Datasheet

080R200-GP3C

Pendant push-button station, remote control, 2+1 holes, yellow



Features

Range	Pendant push-button stations, remote control 200x83 mm
components	With 3 holes Ø 22
Code	080R200-GP3C
Description	Pendant push-button station, remote control, 2+1 holes, yellow
Colour	Giallo RAL1003 / Grigio RAL7035
Weight - gr	280.0
Customs Tariff	85381000
GTIN	8052878064754

Datasheet

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1, IEC-EN60204-1
Operating temperatures	-35° ÷ +80°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK08 (IEC-EN62262)
Housing material	High impact grade thermoplastic polymer
Manufacturing process	Injection moulding
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Screw type	Torx T15 slotted head type
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Cable clamp screw	Tightening torque 1.5Nm (13.3 Lb-in) max.
Pendant fixing ring	Stainless steel AISI 304
Flexible cable gland	M20x1.5 suitable for cable D.6÷12mm
Rated insulation voltage	Ui 300V - Uimp 2.5KV (IEC-EN60947-1)
Protection against electric shock	Class II (IEC-EN61140)
Combustion behaviour	HB (UL94)
Combustion behaviour	650°(IEC-EN60695-2-11)
Fitted for outdoor application	yes
Pushbutton and electrical contacts block	See 020 product range: 020 SM2 D.22mm

Warranty period

18 months

Technical drawings

