

## Scheda Dati

080R200-GP4C  
Estação de controle pendente, controle remoto, 3+1 furos, amarelo



## Caratteristiche

|                  |                                                                   |
|------------------|-------------------------------------------------------------------|
| Gama             | Estações de controle pendentes, controle remoto 200x83 mm         |
| Componente       | Com 4 furos Ø 22                                                  |
| Código           | 080R200-GP4C                                                      |
| Descrição        | Estação de controle pendente, controle remoto, 3+1 furos, amarelo |
| Cor              | Giallo RAL1003 / Grigio RAL7035                                   |
| Peso             | 220,0                                                             |
| Tariffa doganale | 85381000                                                          |
| GTIN             | 8052878051846                                                     |

## Dati tecnici

|                                   |                                                |
|-----------------------------------|------------------------------------------------|
| Approvals                         | CE                                             |
| Compliance with standards         | IEC-ENC60947-1, IEC-EN60947-5-1, IEC-EN60204-1 |
| Operating temperatures            | -35° ÷ +80°C                                   |
| Protection degree                 | IP66 - IP69 (IEC-EN60529)                      |
| Protection against impact         | IK08 (IEC-EN62262)                             |
| Housing material                  | High impact grade thermoplastic polymer        |
| Manufacturing process             | Injection moulding                             |
| Gasket material                   | TPE thermoplastic elastomer                    |
| Screw material                    | Stainless steel AISI 304                       |
| Screw type                        | Torx T15 slotted head type                     |
| Tightening torque                 | 0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in)                   |
| Cable clamp screw                 | Tightening torque 1.5Nm (13.3 Lb-in) max.      |
| Pendant fixing ring               | Stainless steel AISI 304                       |
| Flexible cable gland              | M20x1.5 suitable for cable D.6÷12mm            |
| Rated insulation voltage          | Ui 300V - Uimp 2.5KV (IEC-EN60947-1)           |
| Protection against electric shock | Class II (IEC-EN61140)                         |
| Combustion behaviour              | HB (UL94)                                      |
| Combustion behaviour              | 650°(IEC-EN60695-2-11)                         |
| Fitted for outdoor application    | yes                                            |

|                                          |                                       |
|------------------------------------------|---------------------------------------|
| Pushbutton and electrical contacts block | See 020 product range: 020 SM2 D.22mm |
| Warranty period                          | 18 months                             |

Disegni tecnici

