

Datenblatt

080R200-P4

Hängetaster, Fernbedienung, 4 Bohrungen, grau



Merkmale

| | |
|------------------------|---|
| Baureihe | Hängetaster, Fernbedienung 200x83 mm |
| Komponenten | Mit 4 Bohrungen Ø 22 |
| Artikel-Nr. | 080R200-P4 |
| Beschreibung | Hängetaster, Fernbedienung, 4 Bohrungen, grau |
| Farbe | Grigio RAL7016 / Grigio RAL7035 |
| Gewicht - gr | 278,0 |
| Zolltarifnummer | 85381000 |
| GTIN | 8052878064785 |

Technische Daten

| | |
|---|--|
| Approvals | CE |
| Compliance with standards | IEC-ENC60947-1, IEC-EN60947-5-1, IEC-EN60204-1 |
| Operating temperatures | -35° ÷ +80°C |
| Protection degree | IP66 - IP69 (IEC-EN60529) |
| Protection against impact | IK08 (IEC-EN62262) |
| Housing material | High impact grade thermoplastic polymer |
| Manufacturing process | Injection moulding |
| Gasket material | TPE thermoplastic elastomer |
| Screw material | Stainless steel AISI 304 |
| Screw type | Torx T15 slotted head type |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Cable clamp screw | Tightening torque 1.5Nm (13.3 Lb-in) max. |
| Pendant fixing ring | Stainless steel AISI 304 |
| Flexible cable gland | M20x1.5 suitable for cable D.6÷12mm |
| Rated insulation voltage | Ui 300V - Uimp 2.5KV (IEC-EN60947-1) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Combustion behaviour | HB (UL94) |
| Combustion behaviour | 650°(IEC-EN60695-2-11) |
| Fitted for outdoor application | yes |
| Pushbutton and electrical contacts block | See 020 product range: 020 SM2 D.22mm |
| Warranty period | 18 months |

Technische Zeichnungen

