

## Fiche technique

080R200-P4

Boîtes à boutons pendantes, commande à distance, 4 trous, gris



## Caractéristiques

|                                     |  |
|-------------------------------------|--|
| <b>Portée</b>                       | Boîtes à boutons pendantes, commande à distance 200x83 mm      |
| <b>Composant</b>                    | Avec 4 trous Ø 22  |
| <b>Code</b>                         | 080R200-P4   |
| <b>Désignation des marchandises</b> | Boîtes à boutons pendantes, commande à distance, 4 trous, gris |
| <b>Couleur</b>                      | Grigio RAL7016 / Grigio RAL7035                                |
| <b>Poids</b>                        | 278,0  |
| <b>Tarif douanier</b>               | 85381000   |
| <b>GTIN</b>                         | 8052878064785  |

## Données techniques

|  |  |
|--|--|
| <b>Approvals</b>                         | CE   |
| <b>Compliance with standards</b>         | IEC-ENC60947-1, IEC-EN60947-5-1, IEC-EN60204-1 |
| <b>Operating temperatures</b>            | -35° ÷ +80°C                                   |
| <b>Protection degree</b>                 | IP66 - IP69 (IEC-EN60529)                      |
| <b>Protection against impact</b>         | IK08 (IEC-EN62262)                             |
| <b>Housing material</b>                  | High impact grade thermoplastic polymer        |
| <b>Manufacturing process</b>             | Injection moulding                             |
| <b>Gasket material</b>                   | TPE thermoplastic elastomer                    |
| <b>Screw material</b>                    | Stainless steel AISI 304                       |
| <b>Screw type</b>                        | Torx T15 slotted head type                     |
| <b>Tightening torque</b>                 | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)                    |
| <b>Cable clamp screw</b>                 | Tightening torque 1.5Nm (13.3 Lb-in) max.      |
| <b>Pendant fixing ring</b>               | Stainless steel AISI 304                       |
| <b>Flexible cable gland</b>              | M20x1.5 suitable for cable D.6÷12mm            |
| <b>Rated insulation voltage</b>          | Ui 300V - Uimp 2.5KV (IEC-EN60947-1)           |
| <b>Protection against electric shock</b> | Class II (IEC-EN61140)                         |
| <b>Combustion behaviour</b>              | HB (UL94)                                      |
| <b>Combustion behaviour</b>              | 650°(IEC-EN60695-2-11)                         |
| <b>Fitted for outdoor application</b>    | yes  |

---

**Pushbutton and electrical contacts block**

See 020 product range: 020 SM2 D.22mm

---

**Warranty period**

18 months

---

## Dessins techniques

